

## Beacon Minor - Flood

*Beacon Minor L1 FLD 3K WHT*  
2056166



### PRODUCT OVERVIEW

Product name	Beacon Minor L1 FLD 3K WHT
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4275585
Fixture luminous flux (lm)	623
Luminaire efficacy (lm/W)	47.9
LOR (%)	100
Colour temperature (K)	3000
Beam Angle (°)	25
Total power consumption (W)	13
Electrical protection	Class I
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768561667

### DATA TABLE

#### General data

Product name	Beacon Minor L1 FLD 3K WHT
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4275585

#### Optical data

Fixture luminous flux (lm)	623
----------------------------	-----

## Beacon Minor - Flood

*Beacon Minor L1 FLD 3K WHT*  
2056166

Luminaire efficacy (lm/W)	47.9
LOR (%)	100
Colour temperature (K)	3000
Correlated colour temperature range (K)	3000 - 3000
Adjustable chromaticity	N
Rated Luminous Intensity (cd)	2283
Beam Angle (°)	25

### Electrical data

Total power consumption (W)	13
Mains voltage (V)	230-240V~
Electrical protection	Class I

### Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Height (mm)	151
Weight (kg)	0.47

### Packaging

Single packaging type	Carton
Product EAN number	5025768561667
Packaging single length / height (cm)	25.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	25.0
DUN14 (outer)	05025768561667
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0

## PHOTOMETRY

## TECHNICAL DRAWINGS

