SYLVANIA

ToLEDo Retro Sylone TOLEDO SYLCONE GX200 470LM E27 SL 0027119



Product features

 Unique hand blown glass lamp • Combines contemporary aesthetics and innovative LED filament chip technology (FCT) to create popular retro look and warm ambiance similar to traditional lamps. • Colour temperature of 2000K replicates warm glow effect of incandescent lighting • Dimmable on approved dimmers - allows end user to create perfect ambient lighting • High lumen efficacy of 104lm/W • Environment friendly - no mercury and lower CO2 emissions. • Energy Class: A++ • A range of fittings specifically designed to enhance the aesthetic of the product (only glass and metal visible) are available separately

PRODUCT OVERVIEW

Product name	TOLEDO SYLCONE GX200 470LM E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Round/globe
Туре	ToLEDo Retro Sylone
Cap/Base	E27
General application	Hospitality, Residential & Consumer
ETIM Class	EC001743
E-number SE	8292205
Luminous flux (Im)	470
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	4.5
Average life (Nominal) (h)	15000
Product EAN number	5410288271194

DATA TABLE

General data	
Product name	TOLEDO SYLCONE GX200 470LM E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Round/globe
Туре	ToLEDo Retro Sylone
Cap/Base	E27
General application	Hospitality, Residential & Consumer
ETIM Class	EC001743
E-number SE	8292205
Optical data	
Luminous flux (Im)	470
Luminous flux (Rated) (Im)	470

SYLVANIA

ToLEDo Retro Sylone TOLEDO SYLCONE GX200 470LM E27 SL 0027119

Colour temperature (K)	2000
Light colour	Candlelight
Colour Code	820
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	Ν
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	4.5
Equivalent watt (W)	40
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Mains voltage (V)	220-240V~
Lamp power factor	0.8
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Drive current (mA)	27
kWh per 1000 hours burning time	5
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Nominal) (h) Average life (Rated) (h)	15000 15000
Average life (Rated) (h) Physical data	
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D	15000
Average life (Rated) (h) Physical data	15000 200
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D	15000 200
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging	15000 200 0.255
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type	15000 200 0.255 Carton
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number	15000 200 0.255 Carton 5410288271194
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	15000 200 0.255 Carton 5410288271194 20.6
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 20.6 22.5
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer)	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3 22.9
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 20.6 22.5 15410288271191 2 44.3 22.9
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer length / height (cm) Packaging outer depth (cm) Safety data	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3 22.9 27.5
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer width (cm) Packaging outer depth (cm)	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3 22.9
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DuN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer length / height (cm) Packaging outer depth (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Recommendation for disposal at end of life	15000 200 0.255 Carton 5410288271194 20.6 20.6 22.5 15410288271191 2 44.3 22.9 27.5 Not applicable Not applicable
Average life (Rated) (h) Physical data Max. Lamp Diameter (mm) - D Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer length / height (cm) Packaging outer depth (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Recommendation for disposal at end of	15000 200 0.255 Carton 5410288271194 20.6 20.6 20.6 22.5 15410288271191 2 44.3 22.9 27.5 Not applicable



ToLEDo Retro Sylone TOLEDO SYLCONE GX200 470LM E27 SL 0027119

Suitable for household illumination	Yes	
Suitable for accent lighting	Yes	

TECHNICAL DRAWINGS

