

## Monitor LED


Monitor LED 4000K Emergency Silver  
4055005



### PRODUCT OVERVIEW

Product name	Monitor LED 4000K Emergency Silver
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	Exterior Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC002892
Colour temperature (K)	4000
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Silver
IP rating	IP55
IK rating	IK10
Product EAN number	5026524550055

### PHOTOMETRY




Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	1.56	5.07'	5.07'	189
1.0	3.13	10.14'	10.14'	47
1.5	4.69	15.21'	15.21'	19
2.0	6.26	20.28'	20.28'	11
2.5	7.82	25.35'	25.35'	7
3.0	9.38	30.42'	30.42'	5

Distance [m] Cone diameter [m] Illuminance [lx]  
C0 - C180 (Half beam angle: 114.6°)

## Monitor LED

Monitor LED 4000K Emergency Silver  
4055005



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.56	50° E(C0) 87.4°	998 13
1.0	3.13	50° E(C0) 87.4°	42
1.5	4.69	50° E(C0) 87.4°	19 1
2.0	6.25	50° E(C0) 87.4°	11 1
2.5	7.82	50° E(C0) 87.4°	7 1
3.0	9.38	50° E(C0) 87.4°	5 1

Distance [m] Cone diameter [m]  
C0 - C180 (Half beam angle: 114.8°)

## TECHNICAL DRAWINGS

