
Concord

Beacon LED Projector - Iris Beacon LED Iris Projector O/B 4000K Three Circuit Track - Black 2055971

Product features

 Beacon Projector offers precision light exactly where it is needed. The Iris Projector has an adjusting lever to create a perfect circle of light in the required size. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.




PRODUCT OVERVIEW

Warranty 5 years Fixture luminous flux (Im) 474 Luminaire efficacy (Im/W) 14		
HousingAluminiumMountTrack mountingGeneral applicationHospitality, Museums & GalleriesETIM ClassEC001744E-number FI4260897Warranty5 yearsFixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Product name	Beacon LED Iris Projector O/B 4000K Three Circuit Track - Black
MountTrack mountingGeneral applicationHospitality, Museums & GalleriesETIM ClassEC001744E-number FI4260897Warranty5 yearsFixture luminous flux (lm)474Luminaire efficacy (lm/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Technology	LED
InstrumtHospitality, Museums & GalleriesETIM ClassEC001744E-number Fl4260897Warranty5 yearsFixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Housing	Aluminium
ETIM ClassEC001744E-number FI4260897Warranty5 yearsFixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Mount	Track mounting
E-number FI4260897Warranty5 yearsFixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	General application	Hospitality, Museums & Galleries
Warranty5 yearsFixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	ETIM Class	EC001744
Fixture luminous flux (Im)474Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	E-number FI	4260897
Luminaire efficacy (Im/W)14LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Warranty	5 years
LOR (%)100Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIK20	Fixture luminous flux (Im)	474
Colour temperature (K)4000Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIK02	Luminaire efficacy (Im/W)	14
Light colourNeutral WhiteCRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIK02	LOR (%)	100
CRI (Ra)97Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Colour temperature (K)	4000
Colour Variation Initial (SDCM)SDCM3Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Light colour	Neutral White
Photobiological Risk GroupRG1Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	CRI (Ra)	97
Total power consumption (W)35Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Colour Variation Initial (SDCM)	SDCM3
Product Voltage (V)240Electrical protectionClass IIControl gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Photobiological Risk Group	RG1
Electrical protection Class II Control gear type Electronic ballast Control gear mounting Integral Dimmable Yes Housing colour RAL 9005 - Jet black IP rating IP20 IK rating IK02	Total power consumption (W)	35
Control gear typeElectronic ballastControl gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Product Voltage (V)	240
Control gear mountingIntegralDimmableYesHousing colourRAL 9005 - Jet blackIP ratingIP20IK ratingIK02	Electrical protection	Class II
Dimmable Yes Housing colour RAL 9005 - Jet black IP rating IP20 IK rating IK02	Control gear type	Electronic ballast
Housing colour RAL 9005 - Jet black IP rating IP20 IK rating IK02	Control gear mounting	Integral
IP rating IP20 IK rating IK02	Dimmable	Yes
IK rating IK02	Housing colour	RAL 9005 - Jet black
····-	IP rating	IP20
Product EAN number 5025768559718	IK rating	IK02
	Product EAN number	5025768559718

PHOTOMETRY

Concord

Beacon LED Projector - Iris Beacon LED Iris Projector O/B 4000K Three Circuit Track - Black 2055971



TECHNICAL DRAWINGS

