

## CurveLyte

### CURVELYTE 1265x330 HO D/I 4K DALI BLACK

2093176



#### Product features

- CURVELYTE 1265x330 HO D/I 4K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution. Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Neutral White (4000K) LED Colour Temperature, 6750lm, 55W, 123lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



#### PRODUCT OVERVIEW

Product name	CURVELYTE 1265x330 HO D/I 4K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260865
Warranty	5 years
Fixture luminous flux (lm)	6750
Luminaire efficacy (lm/W)	123
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Housing colour	Black
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931767


#### PHOTOMETRY

## CurveLyte *CURVELYTE 1265x330 HO D/I 4K DALI BLACK* 2093176

0.5	2.13 3.66	E:0° E:C90° E:C0°	4895 175 41
1.0	4.27 7.31	E:0° E:C90° E:C0°	1164 44 11
1.5	6.40 10.97	E:0° E:C90° E:C0°	817 30 5
2.0	8.54 14.63	E:0° E:C90° E:C0°	391 11 3
2.5	10.67 18.28	E:0° E:C90° E:C0°	186 6 2
3.0	12.81 21.93	E:0° E:C90° E:C0°	109 3 1

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 165.8°)  
 — C90 - C270 (Half beam angle: 129.8°)



## TECHNICAL DRAWINGS

