

Start Track Spot Integral

START Track Spot Integral 3000lm 940 MB WB WHT

0005430



Product features

- Integrated LED spotlight, Textured White - RAL9016, simple and slick integral design with no driver box and without any visible screws, ideal for retail applications, die-cast aluminium body, passive cooling heatsink. Beam angle: 36°, additional lens 64° beam angle included, color temperature: 4000k, total system power: 32W, total fixture output: 3000 lm, LOR: 100%, colour rendering: Ra: 90 typical, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 800mA, electronic driver, non-dimmable, ultra low LED flickering rate (5% or less), power factor: >0.90, electrical protection: Class I, Global Track 3 Circuit GA69 adapter suitable for Global trac 3-circuit tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 345°, vertical tilt: 90°, dimensions: Ø80x137x283, weight: 0.880kg.







PRODUCT OVERVIEW

| | |
|---------------------------------|--|
| Product name | START Track Spot Integral 3000lm 940 MB WB WHT |
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Indoor |
| General application | Retail |
| ETIM Class | EC001744 |
| E-number FI | 4276973 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 3000 |
| Luminaire efficacy (lm/W) | 94 |
| Colour temperature (K) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 36 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 32 |
| Electrical protection | Class I |
| Dimmable | No |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK03 |
| Product EAN number | 5410288054308 |

PHOTOMETRY

Start Track Spot Integral
START Track Spot Integral 3000lm 940 MB WB WHT
0005430



TECHNICAL DRAWINGS

