


Beacon LED

BEACON 93CRI 4K MEDIUM BEAM L1 ON-BOARD DIM WHITE
2059607



Product features

- Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 38° medium beam, optics: Aluminium reflector, colour temperature: 4000K neutral white, total system power: 21W, total fixture output: 1885lm, luminaire efficacy: 90lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B50, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 1-circuit track adaptor, suitable for Concord Lytespan 1 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x169mm, weight: 0.96kg.




PRODUCT OVERVIEW

Product name	BEACON 93CRI 4K MEDIUM BEAM L1 ON-BOARD DIM WHITE
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	1885
Luminaire efficacy (lm/W)	90
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Beam Angle (°)	38
Photobiological Risk Group	RG1
Total power consumption (W)	21
Product Voltage (V)	240
Electrical protection	Class II
Control gear type	Electronic ballast
Minimum dimming level (%)	95
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768596072

PHOTOMETRY

Beacon LED

BEACON 93CRI 4K MEDIUM BEAM L1 ON-BOARD DIM WHITE
2059607



0.5	0.35	E(0°) E(C0)	19.85 7028
1.0	0.69	E(0°) E(C0)	4.117 1732
1.5	1.04	E(0°) E(C0)	1.92 779
2.0	1.39	E(0°) E(C0)	1.028 438
2.5	1.73	E(0°) E(C0)	689 282
3.0	2.08	E(0°) E(C0)	457 186

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 33.2°)

TECHNICAL DRAWINGS

