

DeltaWing LED - DALI dimmable

DELTA WING LED72 DALI 4K 1200
0044887



Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 4000K Neutral White, DALI dimmable, 7260lm, 71W, lifespan: 55,000 hours L90B10, A++ A+ A



PRODUCT OVERVIEW

Product name	DELTA WING LED72 DALI 4K 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
E-number FI	4274312
E-number SE	7014038
Warranty	5 years
Fixture luminous flux (lm)	7260
Luminaire efficacy (lm/W)	102.25
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	71
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	95
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448879


DeltaWing LED - DALI dimmable DELTA WING LED72 DALI 4K 1200 0044887

PHOTOMETRY

0.5	1.24 1.64	E(0°) E(C90) E(C180)	8305 1201 862
1.0	2.48 3.28	E(0°) E(C90) E(C180)	2076 288 181
1.5	3.72 4.91	E(0°) E(C90) E(C180)	922 115 88
2.0	4.96 6.55	E(0°) E(C90) E(C180)	619 84 57
2.5	6.20 8.18	E(0°) E(C90) E(C180)	382 41 31
3.0	7.44 9.83	E(0°) E(C90) E(C180)	251 26 18

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 117.2°)
— C90 - C270 (Half beam angle: 102.2°)



TECHNICAL DRAWINGS

