

Brio IP65 LED

BRIO IP55 LED 4k Emergency Silver

4054953



PRODUCT OVERVIEW

Product name	BRIO IP55 LED 4k Emergency Silver
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	Exterior Interior
General application	Education, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC002892
Colour temperature (K)	4000
Control gear mounting	Integral
Housing colour	Silver
IP rating	IP55
IK rating	IK10
Product EAN number	5026524549530

DATA TABLE

General data

Product name	BRIO IP55 LED 4k Emergency Silver
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	Exterior Interior
General application	Education, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC002892

Optical data

Colour temperature (K)	4000
Correlated colour temperature range (K)	4000 - 4000
Adjustable chromaticity	N
Distribution type	Symmetric
Emergency duration (h)	3

Electrical data

Mains voltage (V)	230V~
Control gear mounting	Integral

Brio IP65 LED

BRIO IP55 LED 4k Emergency Silver

4054953

Transformer required	Yes
Drive current (mA)	350



Physical data

Housing colour	Silver
IP rating	IP55
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	White
Nominal Product Length (mm)	408
Nominal Product Width (mm)	358
Weight (kg)	3.2

Packaging

Single packaging type	Carton
Product EAN number	5026524549530
Packaging single length / height (cm)	50.0
Packaging single width (cm)	50.0
Packaging single depth (cm)	20.0
Units per outer package	1
Packaging outer length / height (cm)	50.0
Packaging outer width (cm)	50.0
Packaging outer depth (cm)	20.0

PHOTOMETRY



TECHNICAL DRAWINGS

Brio IP65 LED

BRIO IP55 LED 4k Emergency Silver

4054953

