

## Sylproof Superia LED G3 MW

SYLPROOF SUPERIA LED G3 1200mm Twin 4K DALI E3 MW

0048710



### Product features

- Sylproof Superia, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. L 1278 mm x W 110 mm x H 78 mm size, PC housing, PC diffuser, DALI dimmable, with MW sensor, 3 hour emergency, 4000K, CRI80, 5350 lm, 39 W, 135 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.




### PRODUCT OVERVIEW

Product name	SYLPROOF SUPERIA LED G3 1200mm Twin 4K DALI E3 MW
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	5350
Luminaire efficacy (lm/W)	135
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG1
Total power consumption (W)	39
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487106

### PHOTOMETRY

## Sylproof Superia LED G3 MW SYLPROOF SUPERIA LED G3 1200mm Twin 4K DALI E3 MW 0048710



### TECHNICAL DRAWINGS

