


Brio IP65 LED - Vandal Resistant


BRIO IP55VR LED 4000K
4054980



PRODUCT OVERVIEW

Product name	BRIO IP55VR LED 4000K
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	Exterior Interior
General application	Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC002892
E-number FI	4579202
Colour temperature (K)	4000
Electrical protection	Class II
Control gear mounting	Integral
Housing colour	Black
IP rating	IP55
IK rating	IK10
Product EAN number	5026524549806


PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam type	Illuminance [lx]
0.5	1.56	F01 EC0 C0-C180	809 63
1.0	3.13	F01 EC0 C0-C180	202 16
1.5	4.69	F01 EC0 C0-C180	90 7
2.0	6.25	F01 EC0 C0-C180	45 4
2.5	7.82	F01 EC0 C0-C180	30 3
3.0	9.38	F01 EC0 C0-C180	22 2

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 114.8°)

Brio IP65 LED - Vandal Resistant BRIO IP55VR LED 4000K 4054980



Distance [m]	Cone diameter [m]	EPD EFCB	EPD EFCB	Illuminance [lx]
0.5	1.55	EPD EFCB	82.2°	1499 118
1.0	3.10	EPD EFCB	82.2°	375 30
1.5	4.65	EPD EFCB	82.2°	165 13
2.0	6.21	EPD EFCB	82.2°	93 7
2.5	7.76	EPD EFCB	82.2°	60 5
3.0	9.31	EPD EFCB	82.2°	41 3

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 114.4°)

TECHNICAL DRAWINGS

