

## Sylproof Tubular LED - Microwave sensor

*Sylproof Tubular LED 1X600 EB MW NW*  
0047610



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




### PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X600 EB MW NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	1338
Luminous flux (lm)	1338
Luminaire efficacy (lm/W)	102.92
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	13
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476100

### PHOTOMETRY

## Sylproof Tubular LED - Microwave sensor

*Sylproof Tubular LED 1X600 EB MW NW*  
0047610



Distance (m)	Cone diameter (m)	Beam angle (°)	Beam diameter (m)	Illuminance (lx)
0.5	1.14 1.78	45° 60°	1870 2400	86
1.0	2.28 3.56	45° 60°	438 580	22
1.5	3.41 5.35	45° 60°	188 240	11
2.0	4.55 7.13	45° 60°	104 136	6
2.5	5.69 8.91	45° 60°	67 88	4
3.0	6.83 10.69	45° 60°	46 60	3

Distance (m)      Cone diameter (m)      Illuminance (lx)

— C0 - C180 (Half beam angle: 15.1°)

— C90 - C270 (Half beam angle: 9.74°)

### TECHNICAL DRAWINGS

