

LumiPanel Medium - 210 Ø

Lumipanel Round Medium WW DB
3036768



PRODUCT OVERVIEW

Product name	Lumipanel Round Medium WW DB
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Education, Hospitality, Office, Retail
E-number SE	7099289
E-number Norway	3290572
Fixture luminous flux (lm)	891
Colour temperature (K)	3000
CRI (Ra)	85
Glare control	< 19
Total power consumption (W)	15
Electrical protection	Class III
Control gear mounting	Remote
Minimum dimming level (%)	90
Housing colour	Silver
IP rating	IP44
Product EAN number	8711971367680

DATA TABLE

General data

Product name	Lumipanel Round Medium WW DB
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Education, Hospitality, Office, Retail
E-number SE	7099289
E-number Norway	3290572

Optical data

Fixture luminous flux (lm)	891
----------------------------	-----

LumiPanel Medium - 210 Ø

Lumipanel Round Medium WW DB
3036768

Colour temperature (K)	3000
Correlated colour temperature range (K)	3000 - 3000
CRI (Ra)	85
Adjustable chromaticity	N
Distribution type	Symmetric, Direct
Glare control	< 19

Electrical data

Total power consumption (W)	15
Mains voltage (V)	230V~
Electrical protection	Class III
Control gear mounting	Remote
Transformer required	Yes
Minimum dimming level (%)	90
Drive current (mA)	24
Glow Wire Test (°C)	850

Physical data

Housing colour	Silver
IP rating	IP44
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Cutout Dimensions (W x L in mm or Diameter in mm)	210
Max. Lamp Diameter (mm) - D	223
Weight (kg)	0.53
Recessed Depth (mm)	25

Packaging

Single packaging type	Carton
Product EAN number	8711971367680
Packaging single length / height (cm)	23.6
Packaging single width (cm)	27.0
Packaging single depth (cm)	4.0
Units per outer package	10
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	28.5
Packaging outer depth (cm)	23.0

PHOTOMETRY

LumiPanel Medium - 210 Ø *Lumipanel Round Medium WW DB* 3036768

