

ToLEDo Retro Ball Satin ToLEDo RT BALL V4 ST 470LM 827 B22 SL 0027255



Product features

- · Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- · Same look, size and functionality as incandescent lamps
- · Omni-directional light distribution
- A++ energy rating
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps fits all fixtures
- Environment-friendly no mercury and lower CO2 emissions









PRODUCT OVERVIEW

Product name	ToLEDo RT BALL V4 ST 470LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	4.5
Туре	ToLEDo Retro Ball
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number SE	8295052
Warranty	3 years
Luminous flux (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288272559

DATA TABLE

General data	
Product name	ToLEDo RT BALL V4 ST 470LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	4.5
Туре	ToLEDo Retro Ball
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25



ToLEDo Retro Ball Satin ToLEDo RT BALL V4 ST 470LM 827 B22 SL 0027255

ETIM Class	EC001959
E-number SE	8295052
Warranty	3 years
y	,,,,
Optical data	
Luminous flux (lm)	470
Luminous flux (Rated) (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	4.5
Equivalent watt (W)	40
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2.6
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	38
Max. Luminaires per 16A C Breaker	62
Max. Luminaires per 20A C Breaker	77
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	76.5
Nominal Product Diameter (mm)	45
Weight (kg)	0.021
Packaging	
Single packaging type	Carton
Product EAN number	5410288272559
Packaging single length / height (cm)	9.8
Packaging single width (cm)	4.8
Packaging single depth (cm) DUN14 (inner)	4.8 25410288272553
Units per inner package	6
Packaging inner length / height (cm)	15.3
Packaging inner width (cm)	11.1
r donaging inner width (OIII)	11.1



ToLEDo Retro Ball Satin ToLEDo RT BALL V4 ST 470LM 827 B22 SL 0027255

Packaging inner depth (cm)	10.6
DUN14 (outer)	15410288272556
Units per outer package	60
Packaging outer length / height (cm)	54.7
Packaging outer width (cm)	33.1
Packaging outer depth (cm)	14.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS

