

Sylproof Tubular LED - Microwave sensor

Sylproof Tubular LED 2X1500 EB MW NW
0047615



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X1500 EB MW NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	5821
Luminous flux (lm)	5821
Luminaire efficacy (lm/W)	120.02
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	48
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476155

PHOTOMETRY

Sylproof Tubular LED - Microwave sensor

Sylproof Tubular LED 2X1500 EB MW NW
0047615



0.5	1.16 2.15	E(0°) E(90°) E(180°)	9679 922 238
1.0	2.32 4.33	E(0°) E(90°) E(180°)	1870 223 60
1.5	3.48 6.55	E(0°) E(90°) E(180°)	742 124 28
2.0	4.63 8.73	E(0°) E(90°) E(180°)	411 55 15
2.5	5.79 10.97	E(0°) E(90°) E(180°)	267 37 10
3.0	6.95 13.17	E(0°) E(90°) E(180°)	186 28 7

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 181.0°)
— C90 - C270 (Half beam angle: 98.4°)

TECHNICAL DRAWINGS

