

## HSI-TD

*Hsi-Td 70w/Ndl Uvs Rx7s Slv*

0020231



### PRODUCT OVERVIEW

Product name	Hsi-Td 70w/Ndl Uvs Rx7s Slv
Technology	HID
Watt (Rated) (W)	75
Type	HSI-TD
Cap/Base	RX7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC000037
E-number Norway	3824189
Luminous flux (lm)	5800
Colour temperature (K)	4200
CRI (Ra)	80
Wattage (W)	70
Product Voltage (V)	95
Average life (Nominal) (h)	12000
Product EAN number	5410288202310

### DATA TABLE

#### General data

Product name	Hsi-Td 70w/Ndl Uvs Rx7s Slv
Technology	HID
Watt (Rated) (W)	75
Type	HSI-TD
Cap/Base	RX7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC000037
E-number Norway	3824189

## HSI-TD

*Hsi-Td 70w/Ndl Uvs Rx7s Slv*

0020231

### Optical data

Luminous flux (lm)	5800
Luminous flux (Rated) (lm)	5800
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4200
CRI (Ra)	80
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 4000 h 50Hz	74
Rated lumen maint. factor (%) at 6000 h 50Hz	70
Rated lumen maint. factor (%) at 8000 h 50Hz	68
Rated lumen maint. factor (%) at 12000 h 50Hz	65

### Electrical data

Wattage (W)	70
Current (A)	0.98
Product Voltage (V)	95
Control gear required	Yes
Transformer required	No
kWh per 1000 hours burning time	83

### Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Life T90	8000
Rated survival factor (%) at 2000 h 50Hz	100
Rated survival factor (%) at 4000 h 50Hz	100
Rated survival factor (%) at 6000 h 50Hz	97
Rated survival factor (%) at 8000 h 50Hz	90
Rated survival factor (%) at 12000 h 50Hz	50
Rated survival factor (%) at 16000 h 50Hz	70

### Physical data

Max. Lamp Diameter (mm) - D	22
Weight (kg)	0.021

### Packaging

Single packaging type	Carton
Product EAN number	5410288202310
Packaging single length / height (cm)	20.0
Packaging single width (cm)	3.5
Packaging single depth (cm)	3.5
DUN14 (inner)	15410288202317
Units per inner package	10

## HSI-TD

*Hsi-Td 70w/Ndl Uvs Rx7s Slv*

0020231


Packaging inner length / height (cm)	20.5
Packaging inner width (cm)	18.6
Packaging inner depth (cm)	7.9
DUN14 (outer)	35410288202311
Units per outer package	120
Packaging outer length / height (cm)	49.8
Packaging outer width (cm)	39.5
Packaging outer depth (cm)	23.4

### Safety data

Lamp mercury content (mg)	9.50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	No

## TECHNICAL DRAWINGS

RX7s



HSI-TD	70W	150W	250W
L	117.6	135.4	161.6
D	22	25	27.5