

START Panel G4 625x625

START PANEL HO 625 3000K DALI G4
0047794



Product features

- LED back-lit recessed panel, 3000K Warm White, 4500lm delivered from 36W, 125lm/W total system efficiency, energy efficient external DALI dimmable tridonic driver, even distribution of light throughout fixture, Average lifespan: 100.000Hrs, size (HxWxD) 620x620x65mm.



PRODUCT OVERVIEW

Product name	START PANEL HO 625 3000K DALI G4
Technology	LED
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	120
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	107
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP44/20
IK rating	IK03
Product EAN number	5410288477947


PHOTOMETRY

START Panel G4 625x625 START PANEL HO 625 3000K DALI G4 0047794

0.5	1.07 1.40	E:0° E:C90° E:C0°	6272 407 841
1.0	3.14 2.99	E:0° E:C90° E:C0°	1988 122 135
1.5	4.71 4.48	E:0° E:C90° E:C0°	697 94 85
2.0	6.23 6.98	E:0° E:C90° E:C0°	302 10 54
2.5	7.98 7.47	E:0° E:C90° E:C0°	201 19 27
3.0	9.42 8.98	E:0° E:C90° E:C0°	174 14 15

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 115.0°)
— C90 - C270 (Half beam angle: 115.0°)



TECHNICAL DRAWINGS

