

Granit DALI

Granit IP65 DALI 26000lm 840 WB

0039622

Product features

- Integrated LED highbay; Black aluminium housing; 26000 Lm; 185 W; 140 Lm/W; 4000K; Drive current: 3200mA; CRI 80; 85° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 385 x 194 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.











PRODUCT OVERVIEW

Product name	Granit IP65 DALI 26000lm 840 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4357019
Warranty	5 years
Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	185
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288396224

Granit DALI Granit IP65 DALI 26000lm 840 WB 0039622

PHOTOMETRY



TECHNICAL DRAWINGS

Granit DALI

Granit IP65 DALI 26000lm 840 WB

0039622

