Concord

Beacon LED Projector - Iris Beacon Muse Iris Projector O/B 3000K Three Circuit Track - Black 2055184



Product features

 Beacon Projector offers precision light exactly where it is needed. The Iris Projector has an adjusting lever to create a perfect circle of light in the required size. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.



PRODUCT OVERVIEW

| Product name | Beacon Muse Iris Projector O/B 3000K Three Circuit Track - Black |
|---------------------------------|---|
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Interior |
| General application | Hospitality, Museums & Galleries, Retail |
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Fixture luminous flux (Im) | - |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 97 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 10 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 26 |
| Product Voltage (V) | 240 |
| Electrical protection | Class I |
| Control gear mounting | Integral |
| Housing colour | Black |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5025768551842 |
| Light source included | INTEGRATED LED |

DATA TABLE

| General data | |
|--------------|---|
| Product name | Beacon Muse Iris Projector O/B 3000K Three Circuit Track - Black |
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Interior |

Concord

Beacon LED Projector - Iris Beacon Muse Iris Projector O/B 3000K Three Circuit Track - Black 2055184

| General application | Hospitality, Museums & Galleries, Retail |
|---|---|
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Optical data | |
| Fixture luminous flux (Im) | - |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 97 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Adjustable chromaticity | Ν |
| Beam Angle (°) | 10 |
| Distribution type | Adjustable |
| Photobiological Risk Group | RG1 |
| Electrical data | |
| Total power consumption (W) | 26 |
| Mains voltage (V) | 230V~ |
| Product Voltage (V) | 240 |
| Electrical protection | Class I |
| Control gear mounting | Integral |
| Transformer required | Yes |
| Nominal Frequency (Hz) | 50/60Hz |
| | |
| Lifetime data | |
| Lifetime data Lifespan L70 B50 | 50000 |
| Lifespan L70 B50 | 50000 |
| Lifespan L70 B50 Physical data | |
| Lifespan L70 B50 Physical data Housing colour | Black |
| Lifespan L70 B50 Physical data Housing colour IP rating | Black IP20 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating | Black IP20 IK02 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) | Black IP20 IK02 185 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) | Black IP20 IK02 185 215 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) | Black IP20 IK02 185 215 80 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) | Black IP20 IK02 185 215 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) | Black IP20 IK02 185 215 80 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) | Black IP20 IK02 185 215 80 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging | Black IP20 IK02 185 215 80 1.365 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type | Black IP20 IK02 185 215 80 1.365 Carton |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 32.0 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 32.0 15.5 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 32.0 15.5 13.0 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 32.0 15.5 13.0 05025768551842 |
| Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package | Black IP20 IK02 185 215 80 1.365 Carton 5025768551842 32.0 15.5 13.0 05025768551842 1 |



Beacon LED Projector - Iris Beacon Muse Iris Projector O/B 3000K Three Circuit Track - Black 2055184

TECHNICAL DRAWINGS

