

RefLED ES50 DIMMABLE

RefLED ES50 V5 425lm DIM 865 36° SL 0027467



Product features

• Compact, energy efficient and exceptional value for money product.• Same shape and size as halogen GU10 lamp• Compact Cluster SMD technology enabling high efficiency with halogen look• Reduced visible heat sink from the front• Available in 36 degree• High lumen efficacy• Dimmable with approved dimmers• 15,000 hours average rated life• 3 years warranty













PRODUCT OVERVIEW

Product name	RefLED ES50 V5 425lm DIM 865 36° SL
Technology	LED
Watt (Rated) (W)	5.5
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Warranty	3 years
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	5.5
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288274676

DATA TABLE

General data	
Product name	RefLED ES50 V5 425lm DIM 865 36° SL
Technology	LED
Watt (Rated) (W)	5.5
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years



RefLED ES50 DIMMABLE

RefLED ES50 V5 425lm DIM 865 36° SL 0027467

Optical data	
Rated Luminous Flux Useful (Im)	425
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Rated Luminous Intensity (cd)	1050
Beam Angle (°)	36
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	5.5
Equivalent watt (W)	60
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max)	<1
(s)	
Mains voltage (V)	220-240V~
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
kWh per 1000 hours burning time	6
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
•	
Nominal Product Length (mm)	54
Nominal Product Length (mm) Nominal Product Diameter (mm)	54 50
Nominal Product Length (mm)	54
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg)	54 50
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg)	54 50
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging	54 50 0.038
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type	54 50 0.038 Carton
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number	54 50 0.038 Carton 5410288274676
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	54 50 0.038 Carton 5410288274676 6.1
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	54 50 0.038 Carton 5410288274676 6.1 5.2
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	54 50 0.038 Carton 5410288274676 6.1 5.2
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (inner)	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 5.2 25410288274670
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 5.2 25410288274670 6
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm)	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 25410288274670 6 16.7
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm)	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 25410288274670 6 16.7 11.6
Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm) Packaging inner depth (cm)	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 25410288274670 6 16.7 11.6 7.5
Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm) Packaging inner depth (cm) DUN14 (outer)	54 50 0.038 Carton 5410288274676 6.1 5.2 5.2 25410288274670 6 16.7 11.6 7.5 15410288274673



RefLED ES50 DIMMABLE

RefLED ES50 V5 425lm DIM 865 36° SL 0027467

Packaging outer depth (cm)	17.1
Safety data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS

