

## Sylproof Tubular LED - Microwave sensor DALI

*Sylproof Tubular LED 1X1200 DALI MW WW*  
0047629



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



### PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X1200 DALI MW WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	2629
Luminous flux (lm)	2629
Luminaire efficacy (lm/W)	102.69
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	25.6
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476292


### PHOTOMETRY

## Sylproof Tubular LED - Microwave sensor DALI *Sylproof Tubular LED 1X1200 DALI MW WW* 0047629

0.5	1.17	E:0°	324
	1.60	E:C90°	445
1.0	2.34	E:0°	211
	3.59	E:C90°	311
1.5	3.51	E:0°	141
	5.38	E:C90°	211
2.0	4.68	E:0°	102
	7.15	E:C90°	151
2.5	5.96	E:0°	81
	9.00	E:C90°	121
3.0	7.03	E:0°	69
	10.73	E:C90°	101

Distance [m]      Core diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 12.5°)  
 — C90 - C270 (Half beam angle: 99.0°)



### TECHNICAL DRAWINGS

