

DeltaWing LED - Emergency 3 hour

DELTAWING LED69 EB 3K E3 1200
0044880



Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 3000K Warm White, Electronic, Emergency 3 hour maintained, 6984lm, 74W, lifespan: 55,000 hours L90B10, A++ A+ A



PRODUCT OVERVIEW

Product name	DELTAWING LED69 EB 3K E3 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	6984
Luminaire efficacy (lm/W)	94.37
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 24
Photobiological Risk Group	RG0
Total power consumption (W)	74
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448800
Luminous flux (emergency) (lm)	550

DATA TABLE

DeltaWing LED - Emergency 3 hour DELTAWING LED69 EB 3K E3 1200 0044880

General data

Product name	DELTAWING LED69 EB 3K E3 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
Operating temperature range (°C)	-10°C - 25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	6984
Luminaire efficacy (lm/W)	94.37
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	102
Glare control	< 24
Photobiological Risk Group	RG0
Emergency duration (h)	3.0

Electrical data

Total power consumption (W)	74
Mains voltage (V)	220-240V~
Product Voltage (V)	240
Lamp power factor	0.9
Electrical protection	Class I
Control gear type	Electronic ballast
Transformer required	Yes
Dimmable	No
Drive current (mA)	700
Inrush Current (A)	30
Inrush Duration (µs)	200
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	12
Max. Luminaires per 16A C Breaker	20
Max. Luminaires per 10A B Breaker	12
Max. Luminaires per 16A B Breaker	20

DeltaWing LED - Emergency 3 hour DELTAWING LED69 EB 3K E3 1200 0044880

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	55800

Physical data

Housing colour	White
IP rating	IP44
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1218
Nominal Product Width (mm)	200
Nominal Product Height (mm)	85
Weight (kg)	3.6



Packaging

Single packaging type	Carton
Product EAN number	5410288448800
Packaging single length / height (cm)	122.0
Packaging single width (cm)	9.0
Packaging single depth (cm)	22.5
DUN14 (outer)	05410288448800
Units per outer package	1
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	22.5


Safety data

Optimal operating condition (°C)	-10-25
----------------------------------	--------

PHOTOMETRY



DeltaWing LED - Emergency 3 hour DELTAWING LED69 EB 3K E3 1200 0044880



Distance [m]	Cone diameter [m]	E ₀ ' [lx]	E ₁₀ ' [lx]	E ₃₀ ' [lx]
0.5	1.25 1.44	8972	51.4'	1392
1.0	2.51 2.88	2243	51.4'	272
1.5	3.76 4.32	997	51.4'	121
2.0	5.01 5.76	561	51.4'	66
2.5	6.26 7.19	399	51.4'	44
3.0	7.52 8.63	298	51.4'	33

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Half beam angle: 110.4°)
 C90 - C270 (Half beam angle: 102.8°)

TECHNICAL DRAWINGS

