

DeltaWing LED - Emergency 3 hour

DELTAWING LED69 EB 3K E3 1200
0044880



Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 3000K Warm White, Electronic, Emergency 3 hour maintained, 6984lm, 74W, lifespan: 55,000 hours L90B10, A++ A+ A







PRODUCT OVERVIEW

Product name	DELTAWING LED69 EB 3K E3 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	6984
Luminaire efficacy (lm/W)	94.37
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 24
Photobiological Risk Group	RG0
Total power consumption (W)	74
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448800
Luminous flux (emergency) (lm)	550

PHOTOMETRY

DeltaWing LED - Emergency 3 hour DELTA WING LED69 EB 3K E3 1200 0044880



TECHNICAL DRAWINGS

