

## CurveLyte

*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*

2093186



### Product features

- CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution, with low glare filter (UGR=19). Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Warm White (3000K) LED Colour Temperature, 5000lm, 55W, 91lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



## PRODUCT OVERVIEW

|                             |  |
|-----------------------------|--|
| Product name                | CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK |
| Technology                  | LED  |
| General application         | Education, Hospitality, Office             |
| ETIM Class                  | EC001743                                   |
| E-number FI                 | 4260866                                    |
| E-number SE                 | 7505164                                    |
| Warranty                    | 5 years                                    |
| Fixture luminous flux (lm)  | 5000                                       |
| Luminaire efficacy (lm/W)   | 91   |
| Colour temperature (K)      | 3000                                       |
| Light colour                | Warm White                                 |
| CRI (Ra)                    | 80   |
| Glare control               | < 19                                       |
| Photobiological Risk Group  | RG0  |
| Total power consumption (W) | 55   |
| Electrical protection       | Class I                                    |
| Housing colour              | Black                                      |
| IP rating                   | IP20                                       |
| IK rating                   | IK06                                       |
| Product EAN number          | 5025768931866                              |

## PHOTOMETRY


## CurveLyte

*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*  
2093186

|     |       |       |       |
|-----|-------|-------|-------|
| 0.5 | 1.52  | E:0°  | 400'  |
|     | 1.70  | E:C90 | 65.7" |
|     |       | E:C0  | 339   |
| 1.0 | 3.04  | E:0°  | 1024  |
|     | 3.40  | E:C90 | 65.7" |
|     |       | E:C0  | 339   |
| 1.5 | 4.57  | E:0°  | 485   |
|     | 5.09  | E:C90 | 65.7" |
|     |       | E:C0  | 339   |
| 2.0 | 6.09  | E:0°  | 286   |
|     | 6.75  | E:C90 | 65.7" |
|     |       | E:C0  | 339   |
| 2.5 | 7.61  | E:0°  | 164   |
|     | 8.49  | E:C90 | 65.7" |
|     |       | E:C0  | 339   |
| 3.0 | 9.13  | E:0°  | 114   |
|     | 10.19 | E:C90 | 65.7" |
|     |       | E:C0  | 339   |

Distance [m]      Core diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 113.4°)  
— C90 - C270 (Half beam angle: 113.4°)



## TECHNICAL DRAWINGS

