

## Pixo Mini Track


Pixo Mini TRACK 490lm 927 MB WHITE

0006156



### Product features

- Integrated LED spotlight, Textured White - RAL9016, simple and slick integral design with no driver box and without any visible screws, ideal for retail applications, die-cast aluminium body, passive cooling heatsink. Beam angle: 40°, color temperature: 2700K, total system power: 6.5W, total fixture output: 490 lm, LOR: 100%, colour rendering: Ra: 90 typical, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, low LED flicker rate (6%-20%), power factor: >0.90, electrical protection: Class I, Global Track 3 Circuit GA69 adapter suitable for Global trac 3-circuit tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 345°, vertical tilt: 90°, dimensions: Ø41.5x125, weight: 0.189kg.



## PRODUCT OVERVIEW

Product name	Pixo Mini TRACK 490lm 927 MB WHITE
Technology	LED
Housing	Aluminium
General application	Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4278252
Warranty	5 years
Fixture luminous flux (lm)	490
Luminaire efficacy (lm/W)	75
Colour temperature (K)	2700
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	6.5
Electrical protection	Class I
Dimmable	No
Minimum dimming level (%)	100
LED Flickering Rate	Low (6% - 20%)
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288061566

## DATA TABLE

### General data

Product name	Pixo Mini TRACK 490lm 927 MB WHITE
Technology	LED
Housing	Aluminium
General application	Museums & Galleries, Retail

## Pixo Mini Track

*Pixo Mini TRACK 490lm 927 MB WHITE*

0006156

Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278252
Warranty	5 years

### Optical data

Fixture luminous flux (lm)	490
Luminaire efficacy (lm/W)	75
Colour temperature (K)	2700
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Distribution type	Symmetric
Photobiological Risk Group	RG1

### Electrical data

Total power consumption (W)	6.5
Mains voltage (V)	220-240V~
Lamp power factor	0.5
Electrical protection	Class I
Dimmable	No
Minimum dimming level (%)	100
Drive current (mA)	150
Inrush Current (A)	14
Inrush Duration (µs)	100
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	83
Max. Luminaires per 13A C Breaker	108
Max. Luminaires per 16A C Breaker	133
Max. Luminaires per 20A C Breaker	166
Max. Luminaires per 10A B Breaker	50
Max. Luminaires per 13A B Breaker	65
Max. Luminaires per 16A B Breaker	80
Max. Luminaires per 20A B Breaker	100

### Lifetime data

Lifespan L70 B50	72000
------------------	-------

### Physical data

Housing colour	White
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	Other

## Pixo Mini Track

Pixo Mini TRACK 490lm 927 MB WHITE

0006156

Nominal Product Length (mm)	77
Nominal Product Width (mm)	42
Nominal Product Height (mm)	191
Weight (kg)	0.189


### Packaging

Single packaging type	Carton
Product EAN number	5410288061566
Packaging single length / height (cm)	13.5
Packaging single width (cm)	5.5
Packaging single depth (cm)	13.5
DUN14 (outer)	15410288061563
Units per outer package	32
Packaging outer length / height (cm)	46.0
Packaging outer width (cm)	29.0
Packaging outer depth (cm)	29.0

### Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

## PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	0.55 0.55	E(0°)	18.1"	4582
		E(C90)	19.1"	1903
1.0	0.69 0.70	E(0°)	19.1"	1138
		E(C90)	19.1"	478
1.5	1.04 1.04	E(0°)	19.1"	506
		E(C90)	19.1"	211
2.0	1.39 1.39	E(0°)	19.1"	234
		E(C90)	19.1"	119
2.5	1.73 1.74	E(0°)	19.1"	152
		E(C90)	19.1"	76
3.0	2.08 2.09	E(0°)	19.1"	108
		E(C90)	19.1"	53
		E(0°)	19.2"	55
		E(C90)	19.2"	27

Distance [m] Cone diameter [m] Illuminance [lx]  
 C0 - C180 (Half beam angle: 33.4°)  
 C90 - C270 (Half beam angle: 38.2°)

## TECHNICAL DRAWINGS

