

Expospot 90 cardan square - Sylvania EXPOSPOT 90 DUO HO RA90 4000K WB WHITE 0060389



Product features

Integrated LED double gimbal accent downlight, duo head, ideal for retail and display applications, diecast aluminium body, passive cooling, beam angle: 57°, optics: aluminium reflector and lens combination, colour temperature: 4000K neutral white, total system power: 73W, total fixture output: 2x3479Im, 95Im/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: 60,000 hours at 70% of the original output (L70B50), energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, nondimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148x292mm, dimensions: 163x307x104mm, weight: 2.1kg.




PRODUCT OVERVIEW


| Product name | EXPOSPOT 90 DUO HO RA90 4000K WB WHITE |
|---------------------------------|--|
| Technology | LED |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| Environment | Indoor |
| General application | Retail |
| ETIM Class | EC001744 |
| E-number FI | 4276509 |
| Warranty | 5 years |
| Fixture luminous flux (Im) | 2 x 3479 |
| Luminaire efficacy (Im/W) | 95 |
| LOR (%) | 100 |
| Colour temperature (K) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 57 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 73 |
| Electrical protection | Class II |
| Control gear type | Electronic ballast |
| Control gear mounting | Remote |
| Dimmable | No |
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5410288603896 |
| | |

PHOTOMETRY



Expospot 90 cardan square - Sylvania EXPOSPOT 90 DUO HO RA90 4000K WB WHITE 0060389





TECHNICAL DRAWINGS

