

Sylmaster T5 - PA Louvre

FHE 16 2x35W G5
0055723



Product features

- Sylmaster T5 - PA Louvre




PRODUCT OVERVIEW

Product name	FHE 16 2x35W G5
Technology	Fluorescent
Cap/Base	G5
Housing	Steel
Mount	Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Office, Retail
ETIM Class	EC002892
E-number SE	7098467
E-number Norway	3306309
Warranty	2 years
Fixture luminous flux (lm)	4620
Luminaire efficacy (lm/W)	59
LOR (%)	70
Light colour	N/A
Total power consumption (W)	78
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK07
Product EAN number	5410288557236
Light source included	N/A - Not Applicable

PHOTOMETRY

Sylmaster T5 - PA Louvre FHE 16 2x35W G5 0055723




Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	1.19	1.77	1.19	696
1.0	2.38	3.55	2.38	174
1.5	3.58	5.32	3.58	77
2.0	4.77	7.10	4.77	47
2.5	5.96	8.87	5.96	30
3.0	7.15	10.65	7.15	19

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 121.2°)
 — C90 - C270 (Half beam angle: 100.0°)

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	1.19	1.77	1.19	696
1.0	2.38	3.55	2.38	174
1.5	3.58	5.32	3.58	77
2.0	4.77	7.10	4.77	47
2.5	5.96	8.87	5.96	30
3.0	7.15	10.65	7.15	19

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 121.2°)
 — C90 - C270 (Half beam angle: 100.0°)



TECHNICAL DRAWINGS

Dimensions [mm]	L	I	H	F	Height	Height
1/28W	120	20	85	1000	S	S
2/58W	150	20	85	1000	S	S

