

RefLED ES50 DIMMABLE

RefLED ES50 V5 620Im DIM 865 36° SL 0027469



Product features

- · Compact, energy efficient and exceptional value for money product.
- Same shape and size as halogen GU10 lamp
- Compact Cluster SMD technology enabling high efficiency with halogen look
- Reduced visible heat sink from the front
- Available in 36 degree
- High lumen efficacy
- Dimmable with approved dimmers
- 25,000 hours average rated life
- 3 years warranty













PRODUCT OVERVIEW

Product name	RefLED ES50 V5 620lm DIM 865 36° SL
Technology	LED
Watt (Rated) (W)	7.8
Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
Warranty	3 years
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	7.8
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288274690

DATA TABLE

General data	
Product name	RefLED ES50 V5 620lm DIM 865 36° SL
Technology	LED
Watt (Rated) (W)	7.8
Cap/Base	GU10
Fixture rating	Open
General application	Office, Hospitality, Retail, Education, Residential & Consumer, Museums & Galleries
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959



RefLED ES50 DIMMABLE

RefLED ES50 V5 620lm DIM 865 36° SL 0027469

Warranty	3 years
Optical data	
Rated Luminous Flux Useful (Im)	620
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Rated Luminous Intensity (cd)	1230
Beam Angle (°)	36
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	7.8
Equivalent watt (W)	86
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Product Voltage (V)	230
Lamp power factor	0.8
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
kWh per 1000 hours burning time	8
Nominal Frequency (Hz) Lifetime data	50/60Hz
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
Physical data	
Nominal Product Length (mm)	56
Nominal Product Diameter (mm)	50
Weight (kg)	0.063
0 (0)	
Packaging	
Single packaging type	Carton
Product EAN number	5410288274690
Packaging single length / height (cm)	6.5
Packaging single width (cm)	5.2
Packaging single depth (cm)	5.2
DUN14 (inner)	25410288274694
Units per inner package	6
Packaging inner length / height (cm)	16.7
Packaging inner width (cm)	11.3
Packaging inner depth (cm)	7.5
DUN14 (outer)	15410288274697
Units per outer package	60
Packaging outer length / height (cm)	59.0



RefLED ES50 DIMMABLE

RefLED ES50 V5 620Im DIM 865 36° SL 0027469

Packaging outer width (cm)	18.2
Packaging outer depth (cm)	17.5

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY

TECHNICAL DRAWINGS

