

Presence

ToLEDo PRESENCE A65 1055LM 830 E27 SL
0027547



Product features

- ToLEDo™ Presence - energy saving smart lighting solution • Turn on/off automatically when infrared signal is detected • Operating mode: - Lumen output drops to 50% when no signal is detected for 40 seconds and power consumption also reduces to 6W - Lamp go on stand-by mode when no signal is detected for 60 seconds - Power consumption on stand-by mode is 0.5W • Sensor can pick infrared signal up to maximum distance of 3 meters • 1055lm output equivalent to 75W incandescent lamp • Colour temperature - 3000K • 15,000 hours average rated life • 3 years warranty • The lamp sensor should be free of any obstruction when used in open luminaires • This lamp is not suitable for enclosed luminaires • High colour rendering - CRI80



PRODUCT OVERVIEW

Product name	ToLEDo PRESENCE A65 1055LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	12
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Education, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740599
E-number SE	8294408
Warranty	3 years
Luminous flux (lm)	1055
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	150
Wattage (W)	12
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288275475

DATA TABLE

General data

Product name	ToLEDo PRESENCE A65 1055LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	12
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Education, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740599

Presence

ToLEDo PRESENCE A65 1055LM 830 E27 SL
0027547

E-number SE	8294408
Warranty	3 years

Optical data

Luminous flux (lm)	1055
Luminous flux (Rated) (lm)	1055
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	80
Beam Angle (°)	150

Electrical data

Wattage (W)	12
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.55
No. Of switching cycles before premature failures	>50000
Dimmable	No
kWh per 1000 hours burning time	12
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	125
Nominal Product Diameter (mm)	65
Weight (kg)	0.106

Packaging

Single packaging type	Carton
Product EAN number	5410288275475
Packaging single length / height (cm)	13.0
Packaging single width (cm)	6.5
Packaging single depth (cm)	6.5
DUN14 (inner)	25410288275479
Units per inner package	6
Packaging inner length / height (cm)	20.3
Packaging inner width (cm)	13.7
Packaging inner depth (cm)	13.6
DUN14 (outer)	15410288275472
Units per outer package	60
Packaging outer length / height (cm)	71.5
Packaging outer width (cm)	22.6

Presence

ToLEDo PRESENCE A65 1055LM 830 E27 SL
0027547

Packaging outer depth (cm)	29.9
-----------------------------------	------

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures