Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 3000K Three Circuit Track - Silver 2055180



Product features

Beacon Projector offers precision light exactly where it is needed. The Framing Projector has four adjustable arms allowing the beam to be framed to the desired size shape (square/rectangle or irregular 4 sided shapes). High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.

















| Product name | Beacon Muse Framing Projector O/B 3000K Three Circuit Track - Silver |
|-----------------------------|--|
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Interior |
| General application | Hospitality, Museums & Galleries, Retail |
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | - |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 95 |
| Colour Consistency (SDCM) | 3 |
| Beam Angle (°) | 10 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 26 |
| Product Voltage (V) | 240 |
| Electrical protection | Class II |
| Control gear mounting | Integral |
| Housing colour | Silver |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5025768551804 |
| Light source included | INTEGRATED LED |

DATA TABLE

| General data | |
|--------------|--|
| Product name | Beacon Muse Framing Projector O/B 3000K Three Circuit Track - Silver |



Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 3000K Three Circuit Track - Silver 2055180

| Housing Aluminium Mount Track mounting Environment Interior Ceneral application Hospitality, Museums & Galleries, Retail ETIM Class EC001744 EC | Technology | LED |
|--|--------------------------------------|--|
| Environment Interior General application Hospitality, Museums & Galleries, Retail | Housing | Aluminium |
| General application Hospitality, Museums & Galleries, Retail ETIM Class EC001744 Warranty 5 years Optical data Fixture luminous flux (Im) - Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 95 Colour Consistency (SDCM) 3 Adjustable chromaticity N Beam Angle (*) 10 Distribution type Adjustable Photobiological Risk Group RG1 Electrical data Genumental Control of Cass II Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifetime data Lifetspan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) | Mount | Track mounting |
| ETIM Class EC001744 Syears | Environment | Interior |
| Warranty 5 years Optical data | General application | Hospitality, Museums & Galleries, Retail |
| Optical data | ETIM Class | EC001744 |
| Fixture luminous flux (lm) | Warranty | 5 years |
| Fixture luminous flux (lm) | | |
| Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 95 Colour Consistency (SDCM) 3 Adjustable chromaticity N Beam Angle (*) 10 Distribution type Adjustable Photobiological Risk Group RG1 Electrical data Total power consumption (W) Mains voltage (V) 230V~ Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 Physical data Frequency (Hz) Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1,365 Packaging single length / height (cm) 32,0 Packaging single length | Optical data | |
| Light colour CRI (Ra) 95 Colour Consistency (SDCM) 3 Adjustable chromaticity N Beam Angle (*) 10 Distribution type Adjustable Photobiological Risk Group RG1 Electrical data Total power consumption (W) 26 Mains voltage (V) 230V~ Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IR rating IR Ro2 Nominal Product Width (mm) Nominal Product Height (mm) 185 Nominal Product Diameter (mm) 80 Weight (kg) Light (carton) Product EAN number Product EAN number Packaging single length / height (cm) 13.0 DUN14 (outer) Units per outer package 1 | Fixture luminous flux (lm) | |
| Light colour Warm White CRI (Ra) 95 Colour Consistency (SDCM) 3 Adjustable chromaticity N Beam Angle (*) 10 Distribution type Adjustable Photobiological Risk Group RG1 Electrical data Total power consumption (W) Mains voltage (V) 230V* Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Carton Product EAN number 5025768551804 Packaging single length / height (cm) 13.0 DUN14 (outer) 0.5025768551804 Units per outer package </th <th>Colour temperature (K)</th> <th>3000</th> | Colour temperature (K) | 3000 |
| Colour Consistency (SDCM) Adjustable chromaticity N Beam Angle (*) Distribution type Photobiological Risk Group RG1 Electrical data Total power consumption (W) 26 Mains voltage (V) 230V~ Product Voltage (V) 240 Electrical protection Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IP rating IR rating IR Ro2 Nominal Product Width (mm) 185 Nominal Product Width (mm) 215 Nominal Product Height (mm) 215 Nominal Product Dlameter (mm) 80 Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single length (cm) 13.0 DUN14 (outer) Units per outer package 1 | Light colour | Warm White |
| Adjustable chromaticity Beam Angle (*) Distribution type Photobiological Risk Group RG1 Electrical data Total power consumption (W) Product Voltage (V) Product Voltage (V) Product Voltage (V) Electrical protection Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IP rating IP rating IP rating IN02 Nominal Product Width (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package 1 | CRI (Ra) | 95 |
| Beam Angle (*) 10 10 10 10 10 10 10 1 | Colour Consistency (SDCM) | 3 |
| Beam Angle (*) 10 10 10 10 10 10 10 1 | Adjustable chromaticity | N |
| Electrical data Total power consumption (W) 26 Mains voltage (V) 230V~ Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IR02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package | | 10 |
| Electrical data Total power consumption (W) 26 Mains voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IR02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Prackaging single length / height (cm) 32.0 Packaging single length (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package I 1 | | Adjustable |
| Electrical data Total power consumption (W) 26 Mains voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IR02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Prackaging single length / height (cm) 32.0 Packaging single length (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package I 1 | Photobiological Risk Group | RG1 |
| Total power consumption (W) 26 Mains voltage (V) 230V~ Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | · | |
| Mains voltage (V) 230V° Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifetime data Lifespan L70 B50 50000 Physical data Housing colour IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Electrical data | |
| Mains voltage (V) 230V° Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 Physical data Frequency Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Product EAN number 5025768551804 Packaging single length / height (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Total power consumption (W) | 26 |
| Product Voltage (V) 240 Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | 230V~ |
| Electrical protection Class II Control gear mounting Integral Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IR02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | - · · · | 240 |
| Transformer required Yes Nominal Frequency (Hz) 50/60Hz Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Electrical protection | Class II |
| Lifetime data Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Control gear mounting | Integral |
| Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Transformer required | Yes |
| Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single depth (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Nominal Frequency (Hz) | 50/60Hz |
| Lifespan L70 B50 50000 Physical data Housing colour Silver IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single depth (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | |
| Physical data Housing colour IP rating IP20 IK rating IK02 Nominal Product Width (mm) I85 Nominal Product Height (mm) Veight (kg) Single packaging type Product EAN number Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Silver IP20 IN0 IP20 IN0 IR0 IR0 IR0 IR0 IR0 IR0 IR0 IR0 IR0 IR | Lifetime data | |
| Housing colour IP rating IP20 IK rating IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number Product EAN number Product EAN number 9025768551804 Packaging single length / height (cm) 92.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) Units per outer package 1 | Lifespan L70 B50 | 50000 |
| Housing colour IP rating IP20 IK rating IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number Product EAN number Product EAN number 9025768551804 Packaging single length / height (cm) 92.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) Units per outer package 1 | | |
| IP rating IP20 IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Physical data | |
| IK rating IK02 Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Housing colour | Silver |
| Nominal Product Width (mm) 185 Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | IP rating | IP20 |
| Nominal Product Height (mm) 215 Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | IK rating | IK02 |
| Nominal Product Diameter (mm) 80 Weight (kg) 1.365 Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Nominal Product Width (mm) | 185 |
| Weight (kg)1.365PackagingCartonSingle packaging typeCartonProduct EAN number5025768551804Packaging single length / height (cm)32.0Packaging single width (cm)15.5Packaging single depth (cm)13.0DUN14 (outer)05025768551804Units per outer package1 | Nominal Product Height (mm) | 215 |
| Packaging Single packaging type Carton Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | |
| Single packaging type Product EAN number 5025768551804 Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Carton 32.0 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package | Weight (kg) | 1.365 |
| Single packaging type Product EAN number 5025768551804 Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Carton 32.0 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package | De also sin s | |
| Product EAN number 5025768551804 Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | Packaging | |
| Packaging single length / height (cm) 32.0 Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | Carton |
| Packaging single width (cm) 15.5 Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | 5025768551804 |
| Packaging single depth (cm) 13.0 DUN14 (outer) 05025768551804 Units per outer package 1 | | |
| DUN14 (outer) 05025768551804 Units per outer package 1 | | |
| Units per outer package 1 | | |
| | , , | |
| Packaging outer length / height (cm) 32.0 | | · |
| | Packaging outer length / height (cm) | 32.0 |



Beacon LED Projector - Framing
Beacon Muse Framing Projector O/B 3000K Three Circuit Track - Silver 2055180

15.5 Packaging outer width (cm) Packaging outer depth (cm) 13.0

TECHNICAL DRAWINGS

