

## Sylproof Tubular LED - DALI

*Sylproof Tubular LED 2X1500 DALI NW*  
0047603



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



### PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X1500 DALI NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	5821
Luminous flux (lm)	5821
Luminaire efficacy (lm/W)	120.02
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	48.5
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476032

### PHOTOMETRY


## Sylproof Tubular LED - DALI

*Sylproof Tubular LED 2X1500 DALI NW*  
0047603

0.5	1.16	E:0°	6879
	2.19	E:C90	332
1.0	2.32	E:0°	1810
	4.39	E:C90	332
1.5	3.48	E:0°	124
	6.58	E:C90	29
2.0	4.63	E:0°	117
	8.75	E:C90	15
2.5	5.79	E:0°	287
	10.97	E:C90	11
3.0	6.95	E:0°	198
	13.17	E:C90	7

Distance [m]      Core diameter [m]      Illuminance [lx]

— C90 - C180 (Half beam angle: 13.2°)  
— C90 - C270 (Half beam angle: 86.4°)



## TECHNICAL DRAWINGS

