


## Lynx S

LYNX-S 11W/840 G23 SLV 10  
0025891



### Product features

- Single-bend pin base compact lamp, - Suitable for operation on electronic control gear (SE version), - For use with magnetic ballast (S Version), - Dimmable with suitable ballast, - Excellent colour rendering, - Suitable for emergency lighting



## PRODUCT OVERVIEW

Product name	LYNX-S 11W/840 G23 SLV 10
Technology	Compact Fluorescent
Watt (Rated) (W)	11
Lamp shape	Other
Type	Lynx S
Cap/Base	G23
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944090
E-number SE	8357267
Luminous flux (lm)	900
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	82
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	Not applicable
Wattage (W)	11
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288258911

## DATA TABLE

### General data

Product name	LYNX-S 11W/840 G23 SLV 10
Technology	Compact Fluorescent
Watt (Rated) (W)	11
Lamp shape	Other
Type	Lynx S
Cap/Base	G23
Lamp finish	Frosted/Coated

## Lynx S

LYNX-S 11W/840 G23 SLV 10

0025891

Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944090
E-number SE	8357267

### Optical data

Luminous flux (lm)	900
Luminous flux (Rated) (lm)	900
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	76
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 8000 h 50Hz	75

### Electrical data

Wattage (W)	11
Starting time (max) (s)	10 Sec
Current (A)	0.155
Product Voltage (V)	220
Ignition voltage (V)	186
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	11

### Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72
Rated survival factor (%) at 12000 h 50Hz	62

## Lynx S

*LYNX-S 11W/840 G23 SLV 10*  
0025891

### Physical data

Nominal Product Length (mm)	236
Nominal Product Diameter (mm)	33
Max. Length base to base (mm) - A	236
Max. Lamp Diameter (mm) - D	13
Weight (kg)	0.038


### Packaging

Single packaging type	Carton
Product EAN number	5410288258911
Packaging single length / height (cm)	2.2
Packaging single width (cm)	3.8
Packaging single depth (cm)	24.1
DUN14 (inner)	25410288258915
Units per inner package	10
Packaging inner length / height (cm)	12.4
Packaging inner width (cm)	7.9
Packaging inner depth (cm)	25.6
DUN14 (outer)	15410288258918
Units per outer package	100
Packaging outer length / height (cm)	42.3
Packaging outer width (cm)	27.6
Packaging outer depth (cm)	25.7

### Safety data

Lamp mercury content (mg)	2.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes

## PHOTOMETRY




## TECHNICAL DRAWINGS



# SYLVANIA

Lynx S  
LYNX-S 11W/840 G23 SLV 10  
0025891



**11**  
kWh/1000h



2019/2015

# SYLVANIA

Lynx S  
LYNX-S 11W/840 G23 SLV 10  
0025891



0025891



**11**  
kWh/1000h



2019/2015