


Syl-Line electrical unit SYL-LINE GT3R 4K DALI NR WH EM 0042135



Product features

- Syl-Line LED Gear Tray, 4000K Neutral White, DALI Dimming, Narrow Beam, White, 3 hour Maintained Emergency







PRODUCT OVERVIEW

Product name	SYL-LINE GT3R 4K DALI NR WH EM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
Environment	Interior
General application	Logistics & Industry, Retail
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	6476
Luminous flux (lm)	6476
Luminaire efficacy (lm/W)	119
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0
Total power consumption (W)	54
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	99
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288421353

PHOTOMETRY

Syl-Line electrical unit SYL-LINE GT3R 4K DALI NR WH EM 0042135



TECHNICAL DRAWINGS

