

la de

HSX Syl-Line HSXSYL LED NW EB 1720 WB 0042292

Product features

HSX Syl-Line LED, Neutral White, Electronic, 1720MM, Wide Beam



PRODUCT OVERVIEW

Product name	HSXSYL LED NW EB 1720 WB
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Logistics & Industry, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	6660
Luminaire efficacy (Im/W)	93
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 19
Total power consumption (W)	72
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288422923

DATA TABLE

General data	
Product name	HSXSYL LED NW EB 1720 WB

SYLVANIA

HSX Syl-Line HSXSYL LED NW EB 1720 WB 0042292


Technology	
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Logistics & Industry, Retail
Operating temperature range (°C)	-10°C - 25°C
ETIM Class	EC002892
Warranty	5 years
Optical data	
Fixture luminous flux (Im)	6660
Luminaire efficacy (Im/W)	93
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	Ν
Glare control	< 19
Electrical data	
Total power consumption (W)	72
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear type	Electronic ballast
Transformer required	Yes
Dimmable	No
Drive current (mA)	350
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	С
Nominal Frequency (Hz)	50/60Hz
Dhusiaal data	
Physical data	
Housing colour	White
IP rating	IP20
IK rating	IK02
Diffuser finish	Matt/satinized
Nominal Product Length (mm)	1720
Nominal Product Width (mm)	164
Nominal Product Height (mm)	132
Weight (kg)	5.4
Packaging	
Single packaging type	Carton
Product EAN number	5410288422923
Packaging single length / height (cm)	180.0
Packaging single width (cm)	17.0
i ackaying single width (Chi)	17.0




HSX Syl-Line HSXSYL LED NW EB 1720 WB 0042292

Packaging single depth (cm)	15.0
DUN14 (outer)	05410288422923
Units per outer package	1
Packaging outer length / height (cm)	180.0
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	15.0
Safety data	
Optimal operating condition (°C)	-10-25

PHOTOMETRY





TECHNICAL DRAWINGS