

DeltaWing LED - DALI dimmable & Microwave sensor

DELTAWING LED40 DALI MW 4K 1200
0044895



Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 4000K Neutral White, DALI dimmable, Microwave sensor, 4030lm, 36W, lifespan: 55,000 hours L90B10, A++ A+ A



PRODUCT OVERVIEW

Product name	DELTAWING LED40 DALI MW 4K 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	4030
Luminaire efficacy (lm/W)	111.94
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	103
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	36
Product Voltage (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	95
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448954


PHOTOMETRY

DeltaWing LED - DALI dimmable & Microwave sensor DELTAWING LED40 DALI MW 4K 1200 0044895

Distance [m]	Cone diameter [m]	E0%	E1%	E5%	E10%	E15%	E30%	E50%	E90%	illuminance [lx]
0.5	1.27 1.46	5115	5115	5115	5115	5115	5115	5115	5115	5115
1.0	2.53 2.91	1279	1279	1279	1279	1279	1279	1279	1279	1279
1.5	3.80 4.37	688	688	688	688	688	688	688	688	688
2.0	5.06 5.82	330	330	330	330	330	330	330	330	330
2.5	6.33 7.28	205	205	205	205	205	205	205	205	205
3.0	7.60 8.73	142	142	142	142	142	142	142	142	142

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 115.0°)
 — C90 - C270 (Half beam angle: 103.4°)



TECHNICAL DRAWINGS

