

Expospot 90 cardan square - Sylvania EXPOSPOT 90 DUO HO RA80 3000K MB WHITE 0060352

Product features



• Integrated LED double gimbal accent downlight, duo head, ideal for retail and display applications, diecast aluminium body, passive cooling, beam angle: 44°, optics: aluminium reflector and lens combination, colour temperature: 3000K warm white, total system power: 73W, total fixture output: 2x3721lm, 102lm/W, LOR: 100%, colour rendering: Ra 80 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: 60,000 hours at 70% of the original output (L70B50), energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148x292mm, dimensions: 163x307x104mm, weight: 2.10kg.
















PRODUCT OVERVIEW

| Product name | EXPOSPOT 90 DUO HO RA80 3000K MB WHITE |
|---------------------------------|--|
| Technology | LED |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| Environment | Indoor |
| General application | Retail |
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 2 x 3721 |
| Luminaire efficacy (lm/W) | 102 |
| LOR (%) | 100 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 44 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 73 |
| Electrical protection | Class II |
| Control gear type | Electronic ballast |
| Control gear mounting | Remote |
| Dimmable | No |
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5410288603520 |
| | |

PHOTOMETRY



Expospot 90 cardan square - Sylvania EXPOSPOT 90 DUO HO RA80 3000K MB WHITE 0060352





TECHNICAL DRAWINGS

