

## Sylproof Superia LED G3 DALI

SYLPROOF SUPERIA LED G3 1200mm S 4K DALI  
0048697



### Product features

- Sylproof Superia, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. Polycarbonate housing, Polycarbonate diffuser, DALI dimmable, 4000K, CRI80, 3900 lm, 26 W, 150 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.




### PRODUCT OVERVIEW

Product name	SYLPROOF SUPERIA LED G3 1200mm S 4K DALI
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	3900
Luminaire efficacy (lm/W)	150
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	26
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288486970

### PHOTOMETRY

## Sylproof Superia LED G3 DALI SYLPROOF SUPERIA LED G3 1200mm S 4K DALI 0048697



Distance [m]	Cone diameter [m]	E0° [lx]	E(C90) [lx]	E(C0) [lx]
0.5	1.39 1.27	523	543	623
1.0	2.78 2.53	130	543	160
1.5	4.17 3.80	59	543	69
2.0	5.57 5.06	32	543	39
2.5	6.96 6.33	21	543	29
3.0	8.35 7.60	14	543	17

Distance [m]      Cone diameter [m]  
 — C0 - C180 (Half beam angle: 108.6°)  
 — C90 - C270 (Half beam angle: 108.6°)

### TECHNICAL DRAWINGS

