

ToLEDo Retro Candle Dimmable ToLEDo RT CAND V2 GL DIM 260LM 817 E27 S 0027488



Product features

· Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps • Same look, size and functionality as incandescent lamps. • The combination of innovative filament chip technology and dimming functionality make it an ideal solution for both hospitality application and for general lighting. • Suitable for replacement of 26W incandescent lamp. • A+ energy rating - 58 lm/W • Dimming functionality helps to vary lighting scene as lamps can be dimmed from 100% to 10% and reduces energy consumption as well. • Sparkling light output. • Omnidirectional light distribution. • Environment friendly - no mercury and lower CO2 emissions. • Dimmable on approved dimmers. • Color temperature - 1700K MagmaGlow











PRODUCT OVERVIEW

Product name	ToLEDo RT CAND V2 GL DIM 260LM 817 E27 S
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Candle
Туре	ToLEDo Retro Candle Dimmable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number SE	8292844
Warranty	3 years
Luminous flux (Im)	260
Colour temperature (K)	1700
Light colour	MagmaGlow
CRI (Ra)	80
Beam Angle (°)	320
Wattage (W)	4.5
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288274881

DATA TABLE

General data	
Product name	ToLEDo RT CAND V2 GL DIM 260LM 817 E27 S
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Candle
Туре	ToLEDo Retro Candle Dimmable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	45
ETIM Class	EC001959



ToLEDo Retro Candle Dimmable ToLEDo RT CAND V2 GL DIM 260LM 817 E27 S 0027488

E-number SE	8292844
Warranty	3 years
Optical data	
Luminous flux (lm)	260
Luminous flux (Rated) (Im)	260
Colour temperature (K)	1700
Light colour	MagmaGlow
CRI (Ra)	80
Adjustable chromaticity	N
Beam Angle (°)	320
Electrical data	
Wattage (W)	4.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.8
No. Of switching cycles before premature	>50000
failures	
Transformer required	Yes
Dimmable	Yes
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	92
Nominal Product Diameter (mm)	35
Weight (kg)	0.16
Packaging	
Single packaging type	Carton
	Garton
Product EAN number	5410288274881
Packaging single length / height (cm)	5410288274881 10.5
Packaging single length / height (cm) Packaging single width (cm)	5410288274881 10.5 4.2
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	5410288274881 10.5 4.2 4.2
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner)	5410288274881 10.5 4.2 4.2 25410288274885
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package	5410288274881 10.5 4.2 4.2 25410288274885 6
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm)	5410288274881 10.5 4.2 4.2 25410288274885 6 13.8
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm)	5410288274881 10.5 4.2 4.2 25410288274885 6 13.8 9.4
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm) Packaging inner depth (cm)	5410288274881 10.5 4.2 4.2 25410288274885 6 13.8 9.4 12.5
Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm) Packaging inner width (cm)	5410288274881 10.5 4.2 4.2 25410288274885 6 13.8 9.4




ToLEDo Retro Candle Dimmable ToLEDo RT CAND V2 GL DIM 260LM 817 E27 S 0027488

Packaging outer length / height (cm)	49.5		
Packaging outer width (cm)	29.5		
Packaging outer depth (cm)	15.5		

Safety data

•	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS

