Beacon LED Projector - Gobo

Beacon Muse Gobo Projector O/B 4000K Three Circuit Track - White 2055188



Product features

Beacon Projector offers precision light exactly where it is needed. The Gobo Projector with the use of ROSCO filters allow you to project a still image printed/cut/lasered onto a specially made glass/metal/acetate filter - for example a company logo, text, shapes, images. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.















PRODUCT OVERVIEW

Product name	Beacon Muse Gobo Projector O/B 4000K Three Circuit Track - White
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (Im)	-
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Beam Angle (°)	10
Photobiological Risk Group	RG1
Total power consumption (W)	26
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768551880
Light source included	INTEGRATED LED

DATA TABLE

General data	
Product name	Beacon Muse Gobo Projector O/B 4000K Three Circuit Track - White
Technology	LED
Housing	Aluminium
Mount	Track mounting



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 4000K Three Circuit Track - White 2055188

Environment	
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
0.1.	
Optical data	
Fixture luminous flux (lm)	-
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	10
Distribution type	Adjustable
Photobiological Risk Group	RG1
Electrical data	
Total power consumption (W)	26
Mains voltage (V)	230V~
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Transformer required	Yes
Nominal Frequency (Hz)	50/60Hz
	50/60Hz 50000
Nominal Frequency (Hz) Lifetime data	
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data	50000
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour	
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating	50000 White
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating	50000 White IP20
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm)	50000 White IP20 IK02
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm)	50000 White IP20 IK02 185
Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm)	50000 White IP20 IK02 185 215
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg)	50000 White IP20 IK02 185 215 80
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg)	50000 White IP20 IK02 185 215 80 1.365
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type	50000 White IP20 IK02 185 215 80 1.365
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm)	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5 13.0
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer)	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5 13.0 05025768551880
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5 13.0 05025768551880 1
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5 13.0 05025768551880 1 32.0
Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551880 32.0 15.5 13.0 05025768551880 1



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 4000K Three Circuit Track - White 2055188

TECHNICAL DRAWINGS

