

## Start Highbay DALI

START Highbay IP65 DALI 26000lm 840 MB

0039364



### Product features

- START Highbay, includes 1 m cables, black aluminium housing, 24,700 Lm, 190 W, 130 Lm/W, 4000 K, drive current: 4100 mA, CRI 80, 60° beam angle, DALI dimmable, IP65, IK08, 54,000 hrs (L80/B50), (D x H) 339 x 189 mm, 1 m mains cable, 1 m control cable, 1.2 m chain length including hooks











### PRODUCT OVERVIEW

Product name	START Highbay IP65 DALI 26000lm 840 MB
Technology	LED
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4309001
E-number SE	7214424
Warranty	5 years
Fixture luminous flux (lm)	24700
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	60
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	190
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288393643

### PHOTOMETRY

## Start Highbay DALI START Highbay IP65 DALI 26000lm 840 MB 0039364



### TECHNICAL DRAWINGS

