Myriad Pendant Silver - Remote Gear MYRIAD PENDANT 4000K REMOTE GEAR PHASE DIM SILVER 2049588

Product features

 High-end architectural (4000K) neutral white LED pendant with Phase dimmable driver and remote gear housing, finished in a silver finish (RAL9006)























Product name MYRIAD PENDANT 4000K REMOTE GEAR PHASE DIM SILVER Technology LED Mount Ceiling surface mounting Indoor General application Hospitality, Office, Retail, Residential & Consumer ETIM Class EC001743 Warranty 5 years Fixture luminous flux (Im) Luminaire efficacy (Im/W) LOR (%) Colour temperature (K) Light colour CRI (Ra) Colour Variation Initial (SDCM) Beam Angle (°) Median surface mounting Light colour Retail, Residential & Consumer EC001743 Long (Rea) Long (Rea) Source Neutral White SDCM3 Beam Angle (°) 30		
Mount Ceiling surface mounting Environment Indoor General application Hospitality, Office, Retail, Residential & Consumer ETIM Class EC001743 Warranty 5 years Fixture luminous flux (Im) 1093 Luminaire efficacy (Im/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Product name	
Environment Indoor General application Hospitality, Office, Retail, Residential & Consumer ETIM Class EC001743 Warranty 5 years Fixture luminous flux (Im) 1093 Luminaire efficacy (Im/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Technology	LED
General application ETIM Class EC001743 Warranty 5 years Fixture luminous flux (Im) Luminaire efficacy (Im/W) LOR (%) Colour temperature (K) Light colour CRI (Ra) Colour Variation Initial (SDCM) Hospitality, Office, Retail, Residential & Consumer EC001743 1093 1093 109.3 100 Colour temperature (K) 4000 Neutral White SDCM3	Mount	Ceiling surface mounting
ETIM Class EC001743 Warranty 5 years Fixture luminous flux (Im) 1093 Luminaire efficacy (Im/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Environment	Indoor
Warranty 5 years Fixture luminous flux (lm) 1093 Luminaire efficacy (lm/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	General application	Hospitality, Office, Retail, Residential & Consumer
Fixture luminous flux (Im) 1093 Luminaire efficacy (Im/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	ETIM Class	EC001743
Luminaire efficacy (Im/W) 109.3 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Warranty	5 years
LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Fixture luminous flux (lm)	1093
Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Luminaire efficacy (lm/W)	109.3
Light colourNeutral WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM3	LOR (%)	100
CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3	Colour temperature (K)	4000
Colour Variation Initial (SDCM) SDCM3	Light colour	Neutral White
	CRI (Ra)	80
Beam Angle (°) 30	Colour Variation Initial (SDCM)	SDCM3
	Beam Angle (°)	30

Myriad Pendant Silver - Remote Gear MYRIAD PENDANT 4000K REMOTE GEAR PHASE DIM SILVER 2049588

Total power consumption (W)	10
Electrical protection	Class II
Control gear mounting	Remote
Dimmable	Yes
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Product EAN number	5025768495887

PHOTOMETRY





TECHNICAL DRAWINGS

