


START Panel IP54 UGR19 600x600

START PANEL IP54 U19 600 4100LM 830 DALI
0047786



Product features

- START Panel IP54 is a range of recessed integrated LED panels for general indoor lighting applications such as breakout areas, offices and meeting rooms. Max. drive current: 165mA; Max. power: 36W; Average lifespan: 100.000Hrs; 3000K; CRI 80; Efficacy up to: 121Lm/W; Fixture lumen up to: 4350lm; Glare control <19; IK03; IP44 (from the front); Class II; DALI dimmable.




PRODUCT OVERVIEW

Product name	START PANEL IP54 U19 600 4100LM 830 DALI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
E-number FI	4274202
Warranty	5 years
Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	108
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	90
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP54/20
IK rating	IK03
Product EAN number	5410288477862

PHOTOMETRY

START Panel IP54 UGR19 600x600
START PANEL IP54 U19 600 4100LM 830 DALI
0047786



TECHNICAL DRAWINGS

