

Sylproof Superia LED G3 MW

SYLPROOF SUPERIA LED G3 1500mm Twin 4K DALI E3 MW

0048729



Product features

- Sylproof Superia, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. PC housing, PC diffuser, DALI dimmable, with MW sensor, 3 hour emergency, 4000K, CRI80, 6600 lm, 50 W, 130 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.




PRODUCT OVERVIEW

Product name	SYLPROOF SUPERIA LED G3 1500mm Twin 4K DALI E3 MW
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	6600
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487298

PHOTOMETRY

Sylproof Superia LED G3 MW
SYLPROOF SUPERIA LED G3 1500mm Twin 4K DALI E3 MW
0048729



TECHNICAL DRAWINGS

