

## CurveLyte

### CURVELYTE 1265x330 HO D/I 4K DALI WHITE

#### 2093181



#### Product features

- CURVELYTE 1265x330 HO D/I 4K DALI WHITE is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution. Luminaire Dimensions: 1265x336x46mm, White body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Neutral White (4000K) LED Colour Temperature, 7200lm, 55W, 131lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



## PRODUCT OVERVIEW


Product name	CURVELYTE 1265x330 HO D/I 4K DALI WHITE
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260869
Warranty	5 years
Fixture luminous flux (lm)	7200
Luminaire efficacy (lm/W)	131
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 23
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Housing colour	White
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931811

## PHOTOMETRY

0.5	2.09 3.51	E(0°) E(C90) E(C180)	4779 64.4° 192 48
1.0	4.17 7.02	E(0°) E(C90) E(C180)	1195 64.4° 48 12
1.5	6.26 10.53	E(0°) E(C90) E(C180)	801 64.4° 31 9
2.0	8.35 14.04	E(0°) E(C90) E(C180)	386 64.4° 12 3
2.5	10.44 17.55	E(0°) E(C90) E(C180)	191 64.4° 6 2
3.0	12.52 21.06	E(0°) E(C90) E(C180)	103 64.4° 3 1

Distance [m]      Core diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 145.4°)  
— C90 - C270 (Half beam angle: 128.8°)



## CurveLyte

*CURVELYTE 1265x330 HO D/I 4K DALI WHITE*  
**2093181**

### TECHNICAL DRAWINGS

---

