

Start Waterproof T5 START WATERPROOF T5 PC 1x28 EB 0045827



Product features

Start Waterproof T5 weatherproof luminaire, Polycarbonate housing, Polycarbonate Diffuser, 1 x 28W, Non Dimmable Electronic Ballast, IP66, IK08, Lamp not included, To be used with LFL tubes











PRODUCT OVERVIEW

Product name	START WATERPROOF T5 PC 1x28 EB
Technology	T5 Linear Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	2 years
Light colour	N/A
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288458274

DATA TABLE

General data	
Product name	START WATERPROOF T5 PC 1x28 EB
Technology	T5 Linear Fluorescent
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 25°C
ETIM Class	EC002892
Warranty	2 years
Optical data	
Light colour	N/A
Adjustable chromaticity	N
Electrical data	
Mains voltage (V)	220-240V~
Electrical protection	Class I




Start Waterproof T5 START WATERPROOF T5 PC 1x28 EB 0045827

Control gear type	Electronic ballast
Control gear mounting	Integral
Transformer required	Yes
Nominal Frequency (Hz)	50/60Hz
Physical data	
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1277
Nominal Product Width (mm)	90
Nominal Product Height (mm)	100
Weight (kg)	1.56
D I	

Packaging

0 0	
Single packaging type	Carton
Product EAN number	5410288458274
Packaging single length / height (cm)	127.7
Packaging single width (cm)	9.0
Packaging single depth (cm)	9.3
DUN14 (outer)	05410288458274
Units per outer package	1
Packaging outer length / height (cm)	127.7
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	9.3
Safety data	
Optimal operating condition (°C)	-20-25

PHOTOMETRY



TECHNICAL DRAWINGS



Start Waterproof T5
START WATERPROOF T5 PC 1x28 EB
0045827

