

# Nephos V2 NEPHOS 600 LED V2 BLK NW EB 3097942



#### **Product features**

High-end decorative 600mm diameter neutral white LED pendant with a curved design and diffused (direct) light that provides a soft and ambient lighting effect, finished in a gloss black finish, 2127LM, 24W, 89lm/W, 4000K, Driver Current 700mA, CRI85, non-dimmable, IP20, 50,000hrs (L70)















### PRODUCT OVERVIEW

Product name	NEPHOS 600 LED V2 BLK NW EB
Technology	LED
Housing	Aluminium
Mount	Suspended
Environment	Internal
General application	Hospitality, Retail
ETIM Class	EC001743
E-number FI	4271190
Warranty	5 years
Fixture luminous flux (Im)	2127
Luminaire efficacy (Im/W)	89
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Colour Consistency (SDCM)	5
Glare control	< 20
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	Black
IP rating	IP20
Product EAN number	8711971979425

### **DATA TABLE**

0-			ا ــ ا	
Ge	ner	ัลเ (	ตล	เล

Product name	NEPHOS 600 LED V2 BLK NW EB
Technology	LED
Housing	Aluminium
Mount	Suspended



### Nephos V2 NEPHOS 600 LED V2 BLK NW EB 3097942

Environment	Internal
General application	
Performance ambient temperature Tq	Hospitality, Retail 25
(°C)	
ETIM Class	EC001743
E-number FI	4271190
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	2127
Luminaire efficacy (lm/W)	89
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Colour Consistency (SDCM)	5
Adjustable chromaticity	N
Glare control	< 20
Photobiological Risk Group	RG1
-	
Electrical data	
Total power consumption (W)	24
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class I
Control gear type	Electronic ballast
Transformer required	Yes
Drive current (mA)	700
Inrush Current (A)	25
Inrush Duration (μs)	200
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Max. Luminaires per 16A C Breaker	80
l :fatima data	
Lifetime data	
Lifespan L70 B50	120000
Lifespan L80 B50	112500
Lifespan L90 B50	53500
Physical data	
-	Black
Housing colour IP rating	IP20
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Other
Nominal Product Height (mm)	200
Nominal Product Diameter (mm)	600
Max. Lamp Diameter (mm) - D	600
Weight (kg)	4.8
Weight (kg)	T.U





## Nephos V2 NEPHOS 600 LED V2 BLK NW EB 3097942

#### Packaging

Single packaging type	Carton
Product EAN number	8711971979425
Packaging single length / height (cm)	63.0
Packaging single width (cm)	62.0
Packaging single depth (cm)	28.0
DUN14 (outer)	08711971979425
Units per outer package	1
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	62.0
Packaging outer depth (cm)	28.0

### **PHOTOMETRY**





### **TECHNICAL DRAWINGS**

