

Sylproof Tubular LED - DALI Sylproof Tubular LED 2X600 DALI NW 0047601

Product features



Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED


















PRODUCT OVERVIEW


Product name	Sylproof Tubular LED 2X600 DALI NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (Im)	2269
Luminous flux (Im)	2269
Luminaire efficacy (Im/W)	108.04
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476018

PHOTOMETRY



Sylproof Tubular LED - DALI Sylproof Tubular LED 2X600 DALI NW 0047601





TECHNICAL DRAWINGS

