

ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HO 5FT 5600LM 865

0029518



Product features

- 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp. High switching cycles - 200,000X. High lumen efficacy -151lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HO 5FT 5600LM 865
Technology	LED
Watt (Rated) (W)	37
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740615
E-number SE	8293588
Warranty	5 years
Luminous flux (lm)	5600
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	37
Product Voltage (V)	80
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295183