

Syl-Line electrical unit SYL-LINE GT3R 4K DALI NR WH 0042131

Product features

- Syl-Line LED Gear Tray, 4000K Neutral White, DALI Dimming, Narrow Beam, White



PRODUCT OVERVIEW

Product name	SYL-LINE GT3R 4K DALI NR WH
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
Environment	Interior
General application	Logistics & Industry, Retail
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	6476
Luminous flux (lm)	6476
Luminaire efficacy (lm/W)	128
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0
Total power consumption (W)	50
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	99
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288421315


PHOTOMETRY

Syl-Line electrical unit SYL-LINE GT3R 4K DALI NR WH 0042131

0.5	0.57	E:07	21478
	0.56	E:C90	28.9° 7032
		E:C0	28.1° 7172
1.0	1.15	E:07	5369
	1.11	E:C90	28.9° 1362
		E:C0	28.1° 1792
1.5	1.72	E:07	2388
	1.67	E:C90	28.9° 731
		E:C0	28.1° 727
2.0	2.29	E:07	1312
	2.23	E:C90	28.9° 429
		E:C0	28.1° 448
2.5	2.98	E:07	899
	2.78	E:C90	28.9° 221
		E:C0	28.1° 227
3.0	3.44	E:07	697
	3.24	E:C90	28.9° 198
		E:C0	28.1° 199

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 55.5°)
— C90 - C270 (Half beam angle: 55.6°)



TECHNICAL DRAWINGS

