

## Beacon LED Projector - Iris

*Beacon Muse Iris Projector O/B 4000K Surface Mounted - White*  
2055205



### Product features

- Beacon Projector offers precision light exactly where it is needed. The Iris Projector has an adjusting lever to create a perfect circle of light in the required size. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.



## PRODUCT OVERVIEW

Product name	Beacon Muse Iris Projector O/B 4000K Surface Mounted - White
Technology	LED
Housing	Aluminium
Mount	Ceiling surface mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	-
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	97
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	10
Photobiological Risk Group	RG1
Total power consumption (W)	26
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768552054
Light source included	INTEGRATED LED

## DATA TABLE

### General data

Product name	Beacon Muse Iris Projector O/B 4000K Surface Mounted - White
Technology	LED
Housing	Aluminium

## Beacon LED Projector - Iris

*Beacon Muse Iris Projector O/B 4000K Surface Mounted - White*  
2055205

<b>Mount</b>	Ceiling surface mounting
<b>Environment</b>	Interior
<b>General application</b>	Hospitality, Museums & Galleries, Retail
<b>ETIM Class</b>	EC001744
<b>Warranty</b>	5 years

### Optical data

<b>Fixture luminous flux (lm)</b>	-
<b>Colour temperature (K)</b>	4000
<b>Light colour</b>	Neutral White
<b>CRI (Ra)</b>	97
<b>Colour Variation Initial (SDCM)</b>	SDCM3
<b>Adjustable chromaticity</b>	N
<b>Beam Angle (°)</b>	10
<b>Distribution type</b>	Adjustable
<b>Photobiological Risk Group</b>	RG1

### Electrical data

<b>Total power consumption (W)</b>	26
<b>Mains voltage (V)</b>	230V~
<b>Product Voltage (V)</b>	240
<b>Electrical protection</b>	Class I
<b>Control gear mounting</b>	Integral
<b>Transformer required</b>	Yes
<b>Nominal Frequency (Hz)</b>	50/60Hz

### Lifetime data

<b>Lifespan L70 B50</b>	50000
-------------------------	-------

### Physical data

<b>Housing colour</b>	White
<b>IP rating</b>	IP20
<b>IK rating</b>	IK02
<b>Nominal Product Width (mm)</b>	185
<b>Nominal Product Height (mm)</b>	215
<b>Nominal Product Diameter (mm)</b>	80
<b>Weight (kg)</b>	1.365

### Packaging

<b>Single packaging type</b>	Carton
<b>Product EAN number</b>	5025768552054
<b>Packaging single length / height (cm)</b>	32.0
<b>Packaging single width (cm)</b>	15.5
<b>Packaging single depth (cm)</b>	13.0
<b>DUN14 (outer)</b>	05025768552054
<b>Units per outer package</b>	1
<b>Packaging outer length / height (cm)</b>	32.0
<b>Packaging outer width (cm)</b>	15.5
<b>Packaging outer depth (cm)</b>	13.0

## Beacon LED Projector - Iris

*Beacon Muse Iris Projector O/B 4000K Surface Mounted - White*  
2055205

### TECHNICAL DRAWINGS

---

